



InterLock®

16A.



32A.



63A.



CEE Norm Interlock Socket 380V. 3P+E+N (ABS)

Product Code	Descriptions	IP	Box	Pack
BC1-1403-7540	3/16A. 90° Angled Surface Socket	IP67	1	0
BC1-1403-7560	3/16A. Straight Surface Mounted Socket	IP67	1	0
BC1-1504-7540	4/16A. 90° Angled Surface Socket	IP67	1	0
BC1-1504-7560	4/16A. Straight Surface Mounted Socket	IP67	1	0
BC1-1505-7540	5/16A. 90° Angled Surface Socket	IP67	1	0
BC1-1505-7560	5/16A. Straight Surface Mounted Socket	IP67	1	0
BC1-3403-7540	3/32A. 90° Angled Surface Socket	IP67	1	0
BC1-3504-7540	4/32A. 90° Angled Surface Socket	IP67	1	0
BC1-3505-7540	5/32A. 90° Angled Surface Socket	IP67	1	0
BC1-4504-7540	4/63A. 90° Angled Surface Socket	IP67	1	0
BC1-4505-7540	5/63A. 90° Angled Surface Socket	IP67	1	0



Safety Socket with Misuse Prevention and Device Protection

International Standards: IEC 309-1, IEC 309-2

European Standards: EN 60 309-1, EN 60 309-2

Flame & Fire Resistance: Withstands temperatures exceeding 850°C in the glowing wire test

Mechanical Interlock Switch: Activates only when a plug is inserted

Safety Lock Mechanism: The plug can only be removed when the switch is in the "Off" position

Switch Compatibility: Compliant with IEC 60947, suitable for AC 21, AC 22, and AC 23 applications

Protection Ratings: IP67 (Ingress Protection) & IK8 (Mechanical Impact Protection)

